

2015 PRICE LIST

ARSENFLEX®












Male-Female Connection

Length	Hose Inside Diameter 12mm		Hose Inside Diameter 16mm				Hose Inside Diameter 20mm	
(mm)	1/2"x1/2"		1/2"x3/4"		3/4"x3/4"		1"x1"	
	€/pcs.	\$/pcs.	€/pcs.	\$/pcs.	€/pcs.	\$/pcs.	€/pcs.	\$/pcs.
200	4.3	5.4	5.4	6.7	5.7	7.1	7.2	8.9
250	4.5	5.6	5.7	7.1	6.1	7.6	7.7	9.6
300	4.7	5.8	6.1	7.6	6.5	8.0	8.2	10.3
350	4.8	6.0	6.5	8.0	6.8	8.5	8.8	10.9
400	5.0	6.3	6.8	8.5	7.2	8.9	9.3	11.6
450	5.2	6.5	7.2	8.9	7.5	9.4	9.9	12.3
500	5.4	6.7	7.5	9.4	7.9	9.8	10.4	12.9
600	5.7	7.1	8.2	10.3	8.6	10.7	11.5	14.3
700	6.1	7.6	9.0	11.2	9.3	11.6	12.5	15.6
800	6.5	8.0	9.7	12.1	10.0	12.5	13.6	17.0



Hose: AISI 316L **Stainless Steel**

Fittings: St37 Carbon Steel (CrNi Coated)

Insulation: 9mm Rubber **Insulation Ferrule:** Plastic

Fan Coil Hoses Without Braiding (Insulated)



	Length (mm)	Hose Inside Diameter 12mm		Hose Inside Diameter 16mm				Hose Inside Diameter 20mm	
		1/2"x1/2"		1/2"x3/4"		3/4"x3/4"		1"x1"	
		€/pcs.	\$/pcs.	€/pcs.	\$/pcs.	€/pcs.	\$/pcs.	€/pcs.	\$/pcs.
	200	5.4	6.7	6.8	8.5	7.2	8.9	9.0	11.2
	250	5.6	6.9	7.2	8.9	7.5	9.4	9.5	11.8
	300	5.7	7.1	7.5	9.4	7.9	9.8	10.0	12.5
	350	5.9	7.4	7.9	9.8	8.2	10.3	10.6	13.2
	400	6.1	7.6	8.2	10.3	8.6	10.7	11.1	13.8
	450	6.3	7.8	8.6	10.7	9.0	11.2	11.6	14.5
	500	6.5	8.0	9.0	11.2	9.3	11.6	12.2	15.2
	600	6.8	8.5	9.7	12.1	10.0	12.5	13.3	16.5
	700	7.2	8.9	10.4	12.9	10.8	13.4	14.3	17.9
	800	7.5	9.4	11.1	13.8	11.5	14.3	15.4	19.2

Male Side Threads: Conical thread according to ISO 7-1

Female Side Threads: Cyclindirical thread according to ISO 228-1

Connection Type: According to EN ISO 10806 Production: According to EN ISO 10380

Prices are determined according to FOB/FCA delivery type.